

5.7" Prime View Enclosed Unit

A metal enclosure houses an SLCD board, industrial 12-24 DC input power supply, backlight drive, and panel. Two-part screw-type Phoenix connectors are used for power and communications. The units support both RS232 and RS485 / RS422 interfaces. The enclosure can be easily mounted in a panel, using a rectangular cutout and drilled mounting holes. A compression gasket provides an effective waterproof and dustproof seal. Contact us if you have NEMA 4 requirements.

The 5.7-inch Prime View unit features:

- High-brightness TFT panel.
- High-efficiency LED backlighting.
- Resistive touch screen.
- USB device port for additional flexibility.
- Two RS232 serial ports.
- Perfect for industrial and medical control surfaces.
- Powered by the SLCD6 controller.

How to Get Started

To get started with a 5.7-inch enclosed unit, order product number 50-0101-15 which includes connectors and comes with a CD that contains utility software, sample images, and sample code. Order the optional Enclosed Unit Accessory Kit product number 42-0082-01 for a DB9 data cable and power supply.

Visit our, "How can I get started?" webpage, call 510-770-1417, or email sales@reachtech.com for more information or to order.

Reach Technology, Inc. reserves the right to make changes in design or specification at any time and without notice.



5.7-inch Prime View Enclosed Unit front view

Product Specifications

Product Part Number	50-0101-15
Reach Board Model	SLCD6
Display Manufacturer	Prime View
Display Size and Type	5.7" TFT
Colors	65,536
Display Viewing Area (mm)	86.4 (H) x 115.2 (W)
Horizontal Viewing Angle (degrees)	120 (typ.)
Vertical Viewing Angle (degrees)	50 (Top) 40 (Bottom) (typ.)
Screen Resolution	320x240
Screen Type	QVGA
Display Brightness (cd/m2)	560 (typ.), with touch
Touch Panel Type	Resistive
Operating Temperature	-20°C to 70°C
Storage Temperature	-40°C to 85°C
Supply Voltage	12-24VDC+/-10%
Current Requirement	5.5W max.
Interface Connector	Two part Phoenix type
Serial Interface	RS232 / RS485
Backlight Display	LED
Number of Serial Ports	3
USB Port	Yes
SD Card Slot	No
Microprocessor	16/32 bit CISC
User Flash Memory	4MB
RoHS	Yes