

5.7" Standard Display Module

This module makes integration easy. Each unit comes with an LCD, controller board, backlight driver, and touch screen, integrated and ready to go. The module form factor is designed to ensure long-term product availability.

The 5.7-inch standard unit features:

- QVGA resolution (320x240).
- High-brightness TFT panel.
- High-efficiency LED backlighting.
- Available with or without resistive touch screen.
- USB connectivity for additional flexibility.
- Two RS232 serial ports, one 3.3V CMOS serial port.
- LCD conforms to an industry standard form factor specifically chosen for multi-sourced long lifetime availability.
- Steel bracket makes display easy to mount.
- Powered by the SLCD6 controller.

Download mechanical drawings, panel specifications, controller and software reference manuals, and other resources at reachtech.com/support/product-specific-documentation/51-0101-14.

Get Started with a Development Kit

To get started with a 5.7-inch development kit order product number 52-0101-14 which includes module, cables, sample images, sample code, power supply, and technical support.

Visit our [Evaluate | How Can I Get Started?](#) web page, call 408-754-4176, or email sales@reachtech.com for more information or to place an order.

Reach Technology, a Novanta company, reserves the right to make changes in design or specification at any time and without notice.



5.7-inch Prime View Display Module, front view

Product Specifications

Product Part Number	51-0101-14
Reach Board Model	SLCD6
Display Manufacturer	Prime View
Display Size and Type	5.7" TFT
Horizontal Viewing Angle (degrees)	120 (typ.)
Vertical Viewing Angle (degrees)	50 (Top) 40 (Bottom) (typ.)
Dimensions	6.325" W x 4.12" H x 1.06" D
Resolution	QVGA, 320x240, 16-bit
Orientation	Landscape, Portrait
Display Brightness (cd/m2)	560 (typ.), with touch
Touch Panel Type	Resistive
Operating Temperature	-20°C to 70°C
Storage Temperature	-40°C to 70°C
Power Supply Voltage	5VDC±10%
Current Requirement	850mA max.
Interface Connector	Molex 53261 series
Serial Interface	RS232 / 3.3V CMOS
Backlight Display	LED
Number of Serial Ports	3
USB Port	Yes
SD Card Slot	No
Processor	16/32 bit CISC
Flash Memory	4MB
Sound	Audio Beeper
RoHS 2	Yes